



# DIVE LIGHTS TECLINE T2 / T6

## USER MANUAL

Thank you for choosing Tecline T2 / T6 dive light.

Should you have any questions, please contact us via e-mail: [scubatech@scubatech.pl](mailto:scubatech@scubatech.pl).

### PURPOSE AND FUNCTION

- Tecline T2/T6 dive lights are designed for underwater use.
- To turn the torch on and off, press and hold the control button for 2-3 seconds.
- To switch between the operating modes (100% / 50% / 20%) briefly press the control button.
- A quick, double press on control button activates the "boost" mode. The light output is then 2000 lumens (for Tecline T2) or 6000 lumens (for Tecline T6 torch). Note: the "boost" mode significantly shortens the burning time of the T6 light (over a dozen of minutes).
- The light under the control button indicates the battery status (voltage):
  - green light: 4.2-3.6 V – red light: 3.5-3.2 V – blinking red light: 3.1-2.7 V. The light switches off automatically when the voltage drops to 2.6 V.
- The light can be easily operated with one hand.

### WARNING!

- !) Avoid looking directly into the beam. The light may permanently damage your eyesight.
- !) Avoid using the light out of water. Overheating may damage the LED cell.
- !) Do not open the battery compartment under water. Water in the battery compartment may damage the light and/or the battery. Such damage is not covered by warranty.

### MAINTENANCE AND STORAGE

- The light should be thoroughly rinsed in fresh water after every use.
- All o-rings should be replaced every 12 months.
- The light should be stored in a dry place at room temperature.

### PARAMETERS

- Material: Aluminium T6061 with hard anodised coating
- Source of light: LED cell with a lifetime of 50 000 hours
- Luminous power:
  - Tecline T2: 1500 lumens / 2000 lumens (in „boost” mode)
  - Tecline T6: 2500 lumens / 6000 lumens (in „boost” mode)
- Light temperature: 6000K – 6500K
- Light focus: 8-10°
- Maximum operational depth: 150m
- Control button SS316 with battery status control light
- Modes of operation: 100% - 50% - 20% - additional „boost” mode
- Burning time in the default mode (100% power):
  - Tecline T2: 125min
  - Tecline T6: 75min
- Net weight: 240g (without battery)
- Power supply: Li-Ion Battery 26650



## DIVE LIGHTS TECLINE T2 / T6

### WARRANTY

This product is covered by a two-year warranty (from the date of purchase).

The warranty is valid only if the product was purchased from a Scubatech/Tecline Authorized Dealer. To make sure the complaint will be valid, please provide the complete equipment set together with the proof of purchase.

#### Warranty does not cover:

- loss or damage caused by misuse of the flashlight (including use in chlorinated water without a proper protection),
- visual damage caused by rough handling (e.g. scratches on the outer coating),
- heat or chemical damage,
- overheating caused by the use on the surface,
- damage caused by improper maintenance, storage and/or unauthorized repairs.

### ATTENTION!

- Do not throw used or unwanted electrical and electronic devices into the waste garbage can. When buying new electrical or electronic equipment in a store, you can dispose the used electronic waste at the dealer, remembering, however, to leave the device of the same type and quantity equal to the purchased equipment.
- The visible sign of the crossed-out garbage bin informs that the device cannot be thrown away with the mixed garbage, but should be returned to the collection point for electrical and electronic equipment.
- Please segregate the electronic waste by putting it in designated containers.
- By disposing of the product correctly you will help to protect the environment and human health.
- For more information on recycling, please contact your local city office or city cleaning company.

